

EVERSTAR ENTERPRISE CO.,LIMITED

XIAMEN COLORWIN INDUSTRIAL & TRADE CO., LTD

UNIT # 1721 NO. 3 RIYUAN ERLI, HULI DISTRICT, XIAMEN, CHINA

TEL: 86- 592- 5996943 / FAX: 86-592-5215134

Website:www.itsmachinery.com Email:julina@itsmachinery.com



Sqare Bottom Paper Bag Machine Technical Parameter Comparison

Model	ERFD-190	ERFD-330	ERFD-450	ERFD-450B
Paper Bag Length	190-370mm	270-530mm	270-530mm	380-760mm
Paper Bag width	80-190mm	120-330mm	220-450mm	220-450mm
Paper Bag Bottom width	50-105mm	60-180mm	90-180mm	80-220mm
Paper Thickness	50-130g/m'	60-150g/m''	80-150g/m'	80-150g/m ²
Machine Speed	30-260pcs/min	30-220pcs/min	30-220pcs/min	30-220pcs/min
Production Speed	30-200 pcs/min	30-180pcs/min	30-150pcs/min	30-120pcs/min
Paper Roll width	280-640mm	380-1050mm	660-1290mm	630-1350mm
Roll Paper Diameter	φ1200mm	φ1200mm	φ1300mm	φ1300mm
Inner Diameter Of Paper	φ76mm	φ76mm	φ76mm	φ76mm
Machine Power	380V 3phase 4 line 11.5KW	380v 3phase 4 line 15KW	380V 3phase 4 line15KW	380V 3phase 4 line 17.5KW
Machine Weight	6000kgs	8500kgs	9000kgs	10500kgs
Machine Size	8500x3500x2200mm	10000x3700x2200mm	10000x3800x2200mm	12000x3800x2200mm

Square Bottom Paper Bag Machine With Printing Technical Parameter Comparison

Model	ERFD-190 w 2 Colors /4 Colors	ERFD-330 w 2 Colors/4 Colors	ERFD-450 w 2 Colors/4 Colors	ERFD-450B w 2 Colors/4 Colors
Paper Tube Length	190-370mm	270-530mm	270-530mm	380-760mm
Paper Bag width	80-190mm	120-330mm	220-450mm	220-450mm
Paper Bag Bottom width	50-105mm	70-180mm	80-180mm	80-220mm
Paper Thickness	50-130g/m'	60-150g/m"	80-150g/m'	80-150g/m2
Machine Speed	30-260pcs/min	30-220pcs/min	30-220pcs/min	
Production Speed	30-200 pcs/min	30-180 pcs/min	30-180pcs/min	30-120pcs/min
Paper Roll width	280-640mm	380-1050mm	660-1290mm	650-1410mm
Roll Paper Diameter	φ1300mm	φ1300mm	φ1300mm	φ1300mm
Inner Diameter Of Paper	φ76mm	φ76mm	φ76mm	φ76mm
Printing Area				
Printing width	100-760mm	100-1260mm	100-1260mm	100-1260mm
Printing Length	190-360mm	270-520mm	270-520mm	380-750mm
Printing Speed	5-86m/ min	10-100m/min	10-100m/min	10-100m/min
color Accuracy	≤ ±0.20mm	≤ ±0.20mm	≤ ±0.20mm	≤ ±0.20mm
Plate Thickness	2.28mm+0.38mm (Including The Thickness Of The Double-sided Tape) (Customized By Requirement Of client)			
Working Air Current	≥ 0.36m ³ / minutes, 0.5-0.8 MPa	≥ 0.36m ³ / minutes, 0.5-0.8 MPa	≥ 0.36m ³ / minutes, 0.5-0.8 MPa	≥ 0.36m ³ / minutes, 0.5-0.8 MPa
Printing Machine power	\	380V 3Phase 4 line 8.2kw/11.4k\	\	\
Machine Power	380V 3phase 4 line For 2 Colors 19.7KW For 4 Colors 22.9KW	380v 3phase 4 line For 2 Colors 23.2KW For 4 Colors 26.4KW	380V 3phase 4 line For 2 Colors 23.2KW For 4 Colors 26.4KW	380V 3phase 4 line For 2 Colors 23.5KW For 4 Colors 26.5KW
Machine Size	For 2 Colors 11000mm×3500×2800mm For 4 Colors 17500mm×3500×2800mm	For 2 Colors 16400mmx5000x2500mm For 4 Colors 17700mmx5000x2500mm	For 2 Color 16400mmx5000x2500mm For 4 Color 17700mmx5000x2500mm	For 2 Color 16500mmx5000x2500mm For 4 Color 17800mmx5000x2500mm
Machine Weight	For 2 Colors 7800kgs For 4 Colors 8400kgs	For 2 Colors 10500kgs For 4 Colors 11000kgs	For 2 Colors 11500kgs For 4 Colors 12000kgs	For 2 Colors 12500kgs For 4 Colors 13000kgs